

LSBU18DZ Service temperature wine cellar

Prestige range







Our products are manufactured in compliance with European environmental rules. Especially, refrigerant fluid (R600a) doesn't reject neither CFC nor HFC and respect environment.

Energy consumption is calculated based on the result obtained for 24h in standard test conditions. The actual energy consumption depends on the conditions of use and location of the device.

This equipment is designed to be used in an ambient temperature between 16-38°C

This appliance is intended to be used exclusively for the storage of wine.

Alcohol abuse is dangerous for health, please consume in moderation.

*Capacity given as an indication with 75cl Bordeaux traditional type bottles and measured with 4 shelves. Adding shelves reduce considerably the total capacity.

capacity.

**Thanks to the Vinotag® application, benefit from a digital register of your wine cellar and be alerted of the peak dates of your wines. In partnership with Vivino, scan your bottle to access its pre-filled wine sheet.

Capacity: 18 bottles*:

upper part: 7 bottleslower part: 11 bottles

♣ Vinotag compatible**

Built-under counter installation

 Design: black body & black piano organic glass door frame

Cooling system: compressor

Type of cold: air moving system

+ Adjustable temperature ranges of use:

upper part: 5-12°Clower part: 12-20°C

Electronic regulation

Thermometer with white electronic display

➡ White LED lights with switch button

1 reversible glass door, anti-UV treated,
 2-layers tempered glass (grey-colored)

DESIGN AND ELEGANCE

Built-in under a counter, the LSBU18DZ fits elegantly into your kitchen and easily thanks to its standard 30cm unit format. Protected by a tempered glass door with anti-UV treatment, your bottles are visible and enhanced by interior LED lighting. The full glass door frame and its removable plinth guarantee perfect integration.

TO THE NEAREST DEGREE

Bring your wines to tasting temperature to take full advantage of all their aromas. Thanks to its 2 temperature zones with independent adjustment, you can bring several types of wine to tasting temperature in the same cabinet.

SILENCE & LOW CONSUMPTION

The LSBU18DZ service cellar is classified F (energy class). More respectful and above all more economical, it is also quiet with a sound level of 39 decibels for smarter daily use.



LSBU18DZ Service temperature wine cellar

Prestige range



> EQUIPMENTS INCLUDED

- 4 sliding wooden shelves (beech)
- 4 adjustable feet (height 6.5 cm)
- 1 active charcoal filter
- Anti-vibration system
- Removable ventilation grid

> TECHNICAL CHARACTERISTICS

■ Energy class: F

■ Annual electrical consumption: 96 kWh

Climatic class: N-ST
Noise level: 38 dB
Voltage: 220-240 V
Power input: 58 W
Category: 2 - Wine cellar
Type of gas: R600a

> VINOTAG® APPLICATION

Free wine cellar management application. Access a virtual representation of your wine cellar and a detailed inventory of its contents.

> COMPATIBLE ACCESSORIES

Only available in spare parts

> LOGISTIC DATAS

Gross dimensions (WxDxH cm) : $33 \times 63.5 \times 85.5$ Net dimensions (WxDxH cm) : $29.5 \times 55.5 \times 81.5$

 Gross weight (kg)
 : 30.00

 Net weight (kg)
 : 28.00

 Full truck (pcs)
 : 0

 Container (pcs)
 20' : 148

40' : 303 40' HC : 387

Gencod 3541362304049

Non-contractual pictures Last update: 26/06/2023