

LSBU51DB2 Service temperature wine cellar

Prestige range





Capacity: 51 bottles*: - upper part: 16 bottles - lower part: 35 bottles

Vinotag compatible**

- Built-under counter installation
- Toesign: black body & black piano organic glass door frame
- Cooling system: compressor
- Type of cold: air moving system
- Adjustable temperature ranges of use:

- upper part: 5-12°C - lower part: 12-20°C

- Electronic regulation
- Thermometer with blue digital display
- White LED lights with switch button
- 1 reversible glass door, 2-layers tempered glass

DESIGN AND ELEGANCE

Built-in under a counter, the LSBU51DB2 fits elegantly into your kitchen and easily thanks to its standard 60cm unit format. Protected by a tempered glass door with anti-UV treatment, your bottles are visible and enhanced by interior LED lighting. The full glazed door and its removable plinth guarantee perfect integration.

TO THE NEAREST DEGREE

Bring your wines to tasting temperature to take full advantage of all their aromas. Thanks to its 2 temperature zones with independent adjustment, you can bring several types of wine to tasting temperature in the same cabinet. Equipped with an active carbon filter, the LSBU51DB2 provides an interior filtration and aeration system to guarantee a healthy environment for your wines (FILTER4).

SILENCE & LOW CONSUMPTION

With an energy consumption of only 108 kWh / year, the LSBU51DB2 service cellar is classified F (energy class). More respectful and above all more economical, it is also extremely quiet with a sound level of only 36 decibels for smarter daily use.



Our products are manufactured in compliance with European environmental rules. Especially, refrigerant fluid (R600a) doesn't reject neither CFC nor HFC and respect environment.

Energy consumption is calculated based on the result obtained for 24h in standard test conditions. The actual energy consumption depends on the conditions of use and location of the device.

This equipment is designed to be used in an ambient temperature between

This appliance is intended to be used exclusively for the storage of wine.

Alcohol abuse is dangerous for health, please consume in moderation.

*Capacity given as an indication with 75cl Bordeaux traditional type bottles and measured with 8 shelves. Adding shelves reduce considerably the total

capacity.
**Thanks to the Vinotag® application, benefit from a digital register of your wine cellar and be alerted of the peak dates of your wines. In partnership with Vivino, scan your bottle to access its pre-filled wine sheet.



LSBU51DB2

Service temperature wine cellar

Prestige range



> EQUIPMENTS INCLUDED

- 5 fixed wooden shelves (beech)
- 1 wooden half-shelf (beech)
- 4 adjustable feet (height 6.5 cm)
- 1 active charcoal filter
- Removable ventilation grid

> TECHNICAL CHARACTERISTICS

■ Energy class: F

■ Annual electrical consumption: 108 kWh

Climatic class: SN-ST
 Noise level: 36 dB
 Voltage: 220-240 V
 Power input: 100 W
 Category: 2 - Wine cellar
 Type of gas: R600a

> VINOTAG® APPLICATION

Free wine cellar management application. Access a virtual representation of your wine cellar and a detailed inventory of its contents.

> COMPATIBLE ACCESSORIES

■ Carbon filter (Filtre4)

> LOGISTIC DATAS

Gross dimensions (WxDxH cm) : $65.5 \times 67.5 \times 86.5$ Net dimensions (WxDxH cm) : $59.5 \times 57.5 \times 82$

Gross weight (kg) : 49.00

Net weight (kg) : 43.00

Full truck (pcs) : 0

Container (pcs) 20' : 66

40' : 137 40' HC : 159

Gencod 3541362209108

Non-contractual pictures Last update: 10/02/2023